


TC/SERIES LOUDSPEAKERS | TOTAL CONTROL, TOTAL CUSTOM SOUND



polkaudio[®]

Released by DIBP under the
Freedom of Information Act 1982

SERIES

TC265i, TC625i, TC65i

Mix and match TCi Loudspeakers with Polk Audio® RTi Series speakers to create a voice-matched system that delivers multi-channel realism without the space requirements of traditional speaker systems. TCi speakers are tuned to the "Infinite Baffle" of in-wall space, for surprising bass extension from an in-wall speaker. Easily accessible front panel controls tailor your sound for any installation location.

- Polymer composite cones for wide response & aimable 1" tweeters for detailed highs and excellent imaging.
- PowerPort® Bass Venting extends bass definition; Infinite Baffle Tuning uses the virtual enclosure of in-wall space for superior performance (TC265i & TC65i).
- Boundary Switch flattens response in reflective installation locations; Tweeter Level Switch tailors highs to your room acoustics.
- Durable, moisture-resistant materials, aluminum grilles and stainless, rust-resistant hardware for safe use in bathrooms, kitchens, saunas, even under outdoor eaves.

TC265i

OVERALL DIMENSIONS:
20 3/16" H X 8 1/2" W (52.86CM H X 21.59CM W)
OVERALL FREQUENCY RESPONSE: 33Hz - 27kHz

TC625i

OVERALL DIMENSIONS:
14 5/16" H X 8 1/2" W (36.35CM H X 21.59CM W)
OVERALL FREQUENCY RESPONSE: 35Hz - 25kHz


TC65i

OVERALL DIMENSIONS:
14 5/16" H X 8 1/2" W (36.35CM H X 21.59CM W)
OVERALL FREQUENCY RESPONSE: 32Hz - 27kHz


SEE SPECIFICATIONS FOR MORE DETAILED PRODUCT INFORMATION.




MATTE WHITE (PAINTABLE)



TC265i



TC65i



TC625i

Released by DIBP under the Freedom of Information Act 1982

TC80i, TC620i, TC60i

Use round TCi Loudspeakers anywhere you need high performance sound but don't have the room or the desire for even the smallest of freestanding loudspeakers. TCi Loudspeakers are perfect for use in locations demanding extreme durability because they feature moisture resistant materials. The 15° driver offset (TC80i & TC60i) means more uniform coverage and better imaging; easily accessible user controls let you tailor the sound to your specific installation.

Durable, moisture resistant materials—safe for use in kitchens or baths, even under roof eaves for stealthy outdoor audio applications.

Dynamic Balance® polymer composite cone for smooth response and aimable silk dome tweeter for clear, detailed highs; 15° driver offset for better imaging (TC80i & TC60i).

Paintable, powder-coated aluminum grille.

Boundary Switch flattens response in reflective installation locations; tweeter level switch

tailors highs to your room acoustics.

Timbre-matched to the whole Polk Audio RTi Series of high performance loudspeakers, round TCi models make perfect "invisible" surround speakers.

TC80i

OVERALL DIMENSIONS:

9 5/16" DIAMETER X 5" DEPTH (23.65CM DIAMETER X 12.7CM DEPTH)

OVERALL FREQUENCY RESPONSE: 30Hz - 27kHz

TC620i

OVERALL DIMENSIONS:

9 5/16" DIAMETER X 5" DEPTH (23.65CM DIAMETER X 12.7CM DEPTH)

OVERALL FREQUENCY RESPONSE: 30Hz - 27kHz

TC60i

OVERALL DIMENSIONS:


9 5/16" DIAMETER X 5" DEPTH (23.65CM DIAMETER X 12.7CM DEPTH)

OVERALL FREQUENCY RESPONSE: 30Hz - 27kHz


SEE SPECIFICATIONS FOR MORE DETAILED PRODUCT INFORMATION.




MATTE WHITE (PAINTABLE)



TC80i



TC620i



TC60i



Released by DIBP under the
Freedom of Information Act 1982

CUSTOM INSTALL LOUDSPEAKERS

	TC265i	TC65i	TC625i
Driver Complement	1 - 6 1/2" (16.51cm) Dynamic Balance midrange driver, 1 - 6 1/2" (16.51cm) Dynamic Balance woofer driver, 1 - 1" (2.5cm) Silk Polymer composite dome/ball & socket tweeter	1 - 6 1/2" (16.51cm) Dynamic Balance mid/bass driver, 1 - 1" (2.5cm) cloth dome/ball & socket tweeter	1 - 6 1/2" (16.51cm) Dynamic Balance polymer composite cone driver, 1 - 3/4" (1.91cm) silk dome tweeter
Shape	rectangle	rectangle	rectangle
Frequency Response: Overall / -3dB Limits	30Hz - 27kHz / 45Hz - 25kHz	32Hz - 27kHz / 50Hz - 25kHz	35Hz - 25kHz / 50Hz - 23kHz
Impedance	compatible with 8 Ohms	compatible with 8 Ohms	compatible with 8 Ohms
Recommended Amplification	10 - 200 Watts / channel	10 - 125 Watts / channel	20 - 100 Watts / channel
Efficiency	91dB	90dB	89dB
Available Finish	matte white (paintable)	matte white (paintable)	matte white (paintable)
Product Weight / Shipping Weight	7.1 lbs each / 9.70 lbs each 3.2 kg each / 4.4 kg each	3.85 lbs each / 5.65 lbs each 1.85 kg each / 2.56 kg each	3.45 lbs each / 5 lbs each 1.56 kg each / 2.27 kg each
Overall Dimensions (Depth measured from the deepest component to the back of the baffle)	20 13/16" H x 8 1/2" W x 3 1/2" D (52.86cm H x 21.59cm W x 8.9cm D)	14 5/16" H x 8 1/2" W x 3 3/16" D (36.35cm H x 21.59cm W x 8.096cm D)	14 5/16" H x 8 1/2" W x 3 3/16" D (36.35cm H x 21.59cm W x 8.1cm D)
Depth Assuming 1/2" Drywall	3" (7.6cm)	2 11/16" (6.83cm)	2 11/16" (6.83cm)
Cutout Dimensions	19 3/16" H x 7 1/4" W (48.7cm H x 18.4cm W)	12 3/4" H x 7 1/4" W (32.38cm H x 18.41cm W)	12 3/4" H x 7 1/4" W (32.38cm H x 18.41cm W)
Features	PowerPort®, User Controls	PowerPort®, User Controls	Aimable Tweeter, Rotating Cam Install

CUSTOM INSTALL LOUDSPEAKERS

	TC80i	TC60i	TC620i
Driver Complement	1 - 8" (20.3cm) Dynamic Balance mid/bass driver, 1 - 1" (2.5cm) cloth dome/ball & socket tweeter	1 - 6 1/2" (16.5cm) Dynamic Balance mid/bass driver, 1 - 1" (2.5cm) cloth dome/ball & socket tweeter	1 - 6 1/2" (16.5cm) Dynamic Balance polymer composite cone driver, 1 - 3/4" (1.91cm) silk dome tweeter
Shape	round	round	round
Frequency Response: Overall / -3dB Limits	30Hz - 27kHz / 45Hz - 25kHz	32Hz - 27kHz / 50Hz - 25kHz	35Hz - 25kHz / 50Hz - 23kHz
Impedance	compatible with 8 Ohms	compatible with 8 Ohms	compatible with 8 Ohms
Recommended Amplification	10 - 125 Watts / channel	10 - 125 Watts / channel	20 - 100 Watts / channel
Efficiency	90dB	90dB	89dB
Available Finish	matte white (paintable)	matte white (paintable)	matte white (paintable)
Product Weight / Shipping Weight	3.5 lbs each / 5.35 lbs each 1.6 kg each / 2.43 kg each	3.5 lbs each / 5.15 lbs each 1.6 kg each / 2.34 kg each	3.25 lbs each / 5 lbs each 1.47 kg each / 2.27 kg each
Overall Dimensions	10 5/8" Diameter x 5 5/16" Depth (26.99cm Diameter x 13.5cm Depth)	9 5/16" Diameter x 5 1/16" Depth (23.65cm Diameter x 12.9cm Depth)	9 5/16" Diameter x 4 1/8" Depth (23.65cm Diameter x 10.49cm Depth)
Depth Assuming 1/2" Drywall	4 13/16" (12.2cm)	4 9/16" (11.6cm)	3 5/8" (9.21cm)
Cutout Dimensions	9 3/8" Diameter (23.81cm)	8 3/16" Diameter (20.8cm)	8 3/16" Diameter (20.8cm)
Features	15" Driver Offset, User Controls	15" Driver Offset, User Controls	Aimable Tweeter, Rotating Cam Install

We're fanatics when it comes to providing you useful, accurate information that can help you evaluate our products. But as we all know, we live in an imperfect world. At least some of us do. That's why performance specifications and product dimensions are subject to change without notice. For the most current specifications see our website, www.polkaudio.com/home.

Polk Audio is a Directed Electronics company which trades on NASDAQ under the symbol DEIX. Investor information can be found at <http://investor.directed.com>.

Polk Audio, Polk, PowerPort, Dynamic Balance, F/X, Atrium, Big Speaker Sound Without The Big Speaker, High Velocity Compression Drive, Acoustic Resonance Control, ARC Port, Casket Basket, i-Sonic, SurroundBar & SDA are registered trademarks of Britannia Investment Corporation used under license by Polk Audio, Incorporated. Polk Audio Designs & mDock are trademarks of Britannia Investment Corporation used under license by Polk Audio, Incorporated.



POLK AUDIO
5801 METRO DRIVE
BALTIMORE, MD 21215
WWW.POLKAUDIO.COM
CUSTOMER SERVICE:
800-377-7656 (USA & CANADA)
410-358-3600 (WORLDWIDE)
COPYRIGHT © APRIL 2008
ALL RIGHTS RESERVED.

Released by DIBP under the
Freedom of Information Act 1982